

# **Ceiling Batten Insulation**

Mammoth ceiling batten insulation products are designed to support the thermal performance of skillion or truss ceilings.

Made of 100% polyester, Mammoth® Ceiling Batten Insulation is designed to support the thermal performance of skillion and truss roof spaces. Ceiling batten space is an ideal cavity to insulate:

- to reduce thermal bridging through your truss bottom chords or rafters, and
- as the space is easily accessible from underneath and usually an unused space.

We have two options available for ceiling batten spaces - a R1.0 blanket and R1.3 airlay sections. Both require 45mm deep ceiling battens.

For ceilings with sufficient roof space there is the option of our <u>Mammoth Ceiling Blanket</u> or for new ceilings without a roof space there is the option of our <u>Mammoth Skillion Ceiling Sections</u>.

PRODUCT RANGE						PACK SIZES		
	Туре	Airlay / Card	Density (kg/m3)	R-Value	Nominal thickness (mm)	Dimensions (mm)	Pieces per pack	Area per pack (m2)
Ceiling Batten	Blanket	Card	16.67	R 1.0	45	580 x 12930	2	15
	Section	Airlay	47.10	R 1.0	35	540 x 1200	10	6.48
	Section	Airlay	42.22	R 1.3	45	360 x 2400	9	7.78
	Section	Airlay	42.22	R 1.3	45	560 x 2400	6	8.06

Note: R1.3 sections are for timber framing only.

## **KEY FEATURES**

- Suitable for skillion or truss roofs.
- Semi-rigid Airlay polyester sections (for timber framing only) or Carded polyester blanket.
- 45mm thick sections to fit between ceiling battens.
- Heat-bonded 100% polyester that won't sag or settle over time.
- Sections can easily be cut using wide blade craft knives or specialised insulation saws.
- Self-supporting sections for a smooth friction fit without creases, folds or tucks.
- Also absorbs noise to create a quieter environment.
- Moisture resistant in the event of leaks they continue to perform once dried out.
- Red List Free no glues, resins, formaldehyde or pesticides added.
- Safe and easy to work with non-irritant and non-toxic.
- No precautions are required for handling the product.
- Performance warranted for 50 years (Ts&Cs apply).
- Made in New Zealand by InZone Industries Ltd.

## **TECHNICAL DETAILS**

Technical Attributes	Standard	Test Result
New Zealand Building Code		
✓ Durability	Clause B2.3.1 (a) (b) Clause B2.3.2	Ref: BRANZ Appraisal No. 797 <sup>1</sup>
✓ Internal Moisture	Clause E3.3.1	
✓ Hazardous Building Materials	Clause F2.3.1	
Product Safety		
✓ Non Toxic	OSH Health and Safety Guidelines <sup>2</sup>	Polyester products are 'non-toxic'
✓ Non Irritant	OSH Health and Safety Guidelines <sup>2</sup>	Polyester products are 'non-irritant'
✓ Respiratory Safe	n/a	Polyester fibres are non-respirable
✓ Fire Test	ISO9705	Group1S
✓ VOC Emission Safe <sup>3</sup>	Total VOC ≤ 0.5mg/m <sup>3</sup>	< 0.005mg/m <sup>3</sup> - level below detection <sup>4</sup>
	Formaldehyde ≤ 0.06mg/m <sup>3</sup>	< 0.009mg/m <sup>3</sup> - level below detection
✓ Glue Free		Free from all glues
Other		
✓ Non Corrosive	AS/NZS4859.1	Materials composed entirely of polyester are regarded as non-corrosive and are exempt from testing. Alkalinity of pH 7.8
✓ Vermin Resistant		Not a food source for vermin (and not treated)

<sup>1</sup> Mammoth Ceiling Batten products have the same technical attributes as other Mammoth ceiling products covered by BRANZ Appraisal No 797.

## **INSTALLATION & WARRANTY**

#### Installation

Mammoth Ceiling Batten Insulation must be installed according to the manufacturer's guidelines and in accordance with NZS 4246 (Energy Efficiency - Installing Insulation in Residential Buildings). Installation Instructions for Mammoth Ceiling Insulation can be found at <a href="https://www.mammoth.co.nz/downloads">www.mammoth.co.nz/downloads</a> Contact us on 0800 MAMMOTH for more details.

#### Lifetime Warranty

InZone Industries Ltd (InZone) manufactures Mammoth® 100% polyester insulation products in New Zealand which are designed to provide long-lasting, durable thermal and acoustic insulation. InZone warrant that, provided the polyester insulation is installed correctly and remains adequately protected, Mammoth will perform for the Lifetime\* of the building in which it is installed This Lifetime Manufacturer's Warranty covers insulation material durability when installed in accordance with the manufacturers installation instructions and NZ4246: Energy Efficiency - Installing insulation in residential buildings. Download our Mammoth Insulation Warranty <a href="https://example.com/here-example.com/he

Correct as at 08 May 2025



<sup>2</sup> Occupational Safety and Health Service. Health and Safety Guidelines for the Selection and Safe Handling of Synthetic Mineral Fibres. Dept, of Labour, 1994.

<sup>3</sup> Mammoth has been tested under ASTM D5116. Based on test results for a product with similar nominal weight.

<sup>4</sup> All individual VOCs were less than their threshold limit values. Carcinogens and reproductive toxins were not identified as part of the VOCs.