

Ceiling Blanket Insulation

Mammoth ceiling blankets are designed to be installed in new or existing roof cavities.



An effective and easy form of thermal insulation, Mammoth® Modern Insulation ceiling blankets have a range of R-values of up to R4.0, or R8.0 when double layered. Mammoth blankets are long lasting, won't sag or settle over time, are non-irritant and highly effective. Mammoth products contain recycled polyester fibres. Mammoth ceiling blanket insulation uses up to 7,400 recycled PET plastic bottles per 100sqm*.

For new ceilings without a roof space there is the option of our [Mammoth Skillion Ceiling Sections](#) and for skillion and truss roofs we have [Mammoth Ceiling Battens](#).

Can be double layered to meet the new Building Code.

Mammoth ceiling blankets are manufactured in roll form so that they can be installed as both a single or double layer system. For any system - single or double layered - the joist depth must be greater than the insulation thickness.

Mammoth ceiling blankets are designed in widths to fit snugly between joists or trusses in a single layer option or alternatively with a second layer run perpendicular to the first, covering the top of the joists or truss bottom chord reducing thermal bridging in these areas.

PRODUCT RANGE					PACK SIZES			
			Density (kg/m3)	R-Value	Nominal thickness (mm)	Dimensions (mm)	Pieces per pack	Area per pack (m2)
Ceiling Blanket	✓	✓	7.83	R 1.8	115	870 x 11495	2	20
	✓	✓	7.57	R 2.9	185	870 x 8620	2	15
	✓	✓	8.00	R 3.2	200	870 x 8620	2	15
	✓	✓	8.00	R 3.3	210	870 x 8620	2	15
	✓	✓	8.00	R 3.6	225	870 x 7470	2	13
	✓	✓	8.33	R 4.0	240	870 x 5750	2	10
Double Layer - R 2.9 x 2	✓		7.57	R 5.8	370	870 x 8620	2	15*
Double Layer - R 3.2 x 2	✓		8.00	R 6.4	400	870 x 8620	2	15*
Double Layer - R 3.3 x 2	✓		8.00	R 6.6	420	870 x 8620	2	15*
Double Layer - R 3.6 x 2	✓		8.00	R 7.2	450	870 x 7470	2	13*
Double Layer - R 4.0 x 2	✓		8.33	R 8.0	480	870 x 5750	2	10*

For any system - single or double layered - the joist depth must be greater than the insulation thickness.

* For Double Layering - Double the quantity of product is required. For instance, a 100m2 area requires 200m2 of product to achieve a double layer.

KEY FEATURES

- Soft, roll-form 100% polyester insulation blanket for ceilings. Can be double layered for higher R-value.
- Mammoth ceiling blanket insulation uses up to 7,400 recycled PET plastic bottles per 100sqm*. * Calculations are based on 500ml PET Bottles (16.2g).
- Unaffected by moisture, Mammoth will continue to perform once dried out. Mammoth is moisture, mould and mildew resistant.
- Lightweight and easy to handle - can easily be torn to length or cut with shears. Available in varying widths and lengths to suit most applications.
- Heat bonded - no glues or binders that can break down so it won't sag or settle over time.
- Red List Free - no formaldehyde or pesticides added.
- Safe, non-itch, odourless and non-toxic - no precautions are required for handling the product.
- All Mammoth ceiling blankets are BRANZ 797 Appraised.
- All Mammoth ceiling blankets have Eco Choice Aotearoa (prev. Environmental Choice) certification.
- Mammoth products are made in a zero waste production process and are fully recyclable.
- Mammoth ceiling insulation products have an ODP of zero.
- Long lasting, Mammoth insulation is performance warranted for 50 years (T&Cs apply).

- Manufactured by InZone Industries Ltd, a NZ Toitū carbonreduce certified insulation manufacturing organisation.

TECHNICAL DETAILS

Technical Attributes	Standard	Test Result
New Zealand Building Code		
✓ Durability	Clause B2.3.1 (a) (b) Clause B2.3.2	Ref: BRANZ Appraisal No 797 ¹
✓ Internal Moisture	Clause E3.3.1	Ref: BRANZ Appraisal No 797 ¹
✓ Hazardous Building Materials	Clause F2.3.1	Ref: BRANZ Appraisal No 797 ¹
✓ Energy Efficiency	Clause H1.3.1(a) Clause H1.3.2 E	Ref: BRANZ Appraisal No 797 ¹
Product Safety		
✓ Non Toxic	OSH Health and Safety Guidelines ²	Polyester products are 'non-toxic'
✓ Non Irritant	OSH Health and Safety Guidelines ²	Polyester products are 'non-irritant'
✓ Respiratory Safe	n/a	Polyester fibres are non-respirable
✓ Fire Test	AS/NZS60695.2.11 AS/NZS60695.11.5 ISO9705	Passed - Glow wire flammability test Passed - Test flames (Needle-flame test) Group1S Can safely cover IC-rated downlights. If luminare rating is unknown, minimum clearance of 100mm to any insulation is required.
✓ VOC Emission Safe ³	Total VOC ≤ 0.5mg/m ³ Formaldehyde ≤ 0.06mg/m ³	< 0.005mg/m ³ - level below detection ⁴ < 0.009mg/m ³ - level below detection
✓ Glue Free		Free from all glues
Other		
✓ Non Corrosive	AS/NZS4859.1	Materials composed entirely of polyester are regarded as non-corrosive and are exempt from testing. Alkalinity of pH 7.8
✓ Vermin Resistant		Not a food source for vermin (and not treated)

¹ Meet or contribute to these provisions when designed, used, installed and maintained in accordance with BRANZ Appraisal 797.

² Occupational Safety and Health Service. Health and Safety Guidelines for the Selection and Safe Handling of Synthetic Mineral Fibres, Dept of Labour, 1994.

³ Mammoth has been tested under ASTM D5116. Based on test results for a product with similar nominal weight.

⁴ All individual VOCs were less than their threshold limit values. Carcinogens and reproductive toxins were not identified as part of the VOCs.

INSTALLATION & WARRANTY

Installation

Mammoth Ceiling Insulation must be installed according to the manufacturer's guidelines and in accordance with NZS 4246 (Energy Efficiency - Installing Insulation in Residential Buildings). Installation Instructions for Mammoth Ceiling Insulation can be found [here](#). Contact us on 0800 MAMMOTH for more details.

Lifetime Warranty

InZone Industries Ltd (InZone) manufactures Mammoth® 100% polyester insulation products in New Zealand which are designed to provide long-lasting, durable thermal and acoustic insulation. InZone warrant that, provided the polyester insulation is installed correctly and remains adequately protected, Mammoth will perform for the Lifetime* of the building in which it is installed This Lifetime Manufacturer's Warranty covers insulation material durability when installed in accordance with the manufacturers installation instructions and NZ4246: Energy Efficiency - Installing insulation in residential buildings. Download our Mammoth Insulation Warranty [here](#).

BRANZ Appraised

Mammoth Ceiling Insulation Blanket has been tested by, and is covered by BRANZ Appraisal 797.

Correct as at 08 May 2025